

## KLB-SYSTEM VERDÜNNER UND REINIGER VR 28

Solvent mixture adapted to thinning and cleaning - primarily polyurethane resin sealers

### Packaging units

Article no.	Packaging	Content (kg)	Units/pallet
VR9000-55	Canister	10.00	50



### Product characteristics

Classification	highly flammable
----------------	------------------

### Product description

Solvent mixture aligned with polyurethane resin sealers. Use as thinner of polyurethane sealers which contain solvents (**PU 880, PU 881, PU 881 EL+, PU 882**, and so on), as well as for epoxy resin sealers (**EP 860, EP 861**, and others) within the manufacturers recommendations. For cleaning tools as long as the resins have not yet hardened.

### Technical data

Density	0.9	kg/l	DIN EN ISO 2811-2 (20 °C / 68 °F)
Flashpoint	30 °C / 86	°F	DIN EN ISO 1523 / ISO 2719

The values established in tests are average values. Deviations from the product specification may occur.

### Processing

To clean tools, remove the necessary amount into a separate, reclosable container and carry out the cleaning with a brush. Only dilute sealers according to the manufacturer's recommendation in the correct dosage.

### Storage

Always re-seal and close tight after usage and store closed in a dry place. Please note the safety data sheet!

**Special remarks**

Flammable. Note the information on the containers and on the safety data sheet.

---



Please consider the latest version of this product information on our website.

---

All stated information is based on our experience and technical preparation. We guarantee the correct and proper quality of our products. We do not assume any responsibility for the work not carried out by us, since we have no influence on the processing or processing conditions. We recommend on-site trials to be conducted. With appearance of this new KLB product information, all prior information loses validity. The updated version is available on our website [www.klb-koetzal.com](http://www.klb-koetzal.com). In addition, our "General Terms and Conditions" apply.

---