

# CHEMORESIN PU-BETON 4004



According Attachment III Regulation (EG) No. 305/2011 (Building Product Regulation)

**1. Unique identification  
code for the product  
type:**

EN 13813:2003-01 - PU-Beton4004-V1-092023

**Type, batch or serial  
number or any other  
element allowing  
identification of the  
building product as  
required according to  
article 11 (4):**

Batch number: see label of the product

**Intended use or usage  
of the building product,  
in accordance with the  
applicable harmonised  
technical specification,  
as intended by the  
manufacturer:**

EN 13813: Synthetic resin screed mortar for internal use

**Name, registered trade  
name or registered  
trade mark and contact  
address of the  
manufacturer as  
required according to  
article 11 (5):**

KLB Kötztal Lacke + Beschichtungen GmbH  
Günztalstraße 25  
89335 Ichenhausen  
GERMANY

**System or systems for  
evaluation and  
verification of  
performance reliability  
for the building product  
according to annex V:**

EN 13813:  
System 4 (for internal use)  
System 4 (for internal use subject to fire-behaviour regulations)

**Notified Bodies (N):**

EN 13813, System 4: -

**In case of the  
declaration of  
performance  
concerning a building  
product for which a**

Not relevant

European Technical  
Assessment has been  
issued:

Declared performance:

Harmonised technical specification	EN 13813:2003-01
------------------------------------	------------------

The performance of the  
product according to  
point 1 and 2 conforms  
with the declared  
performance in point 9.  
This declaration of  
performance is issued  
under the sole  
responsibility of the  
manufacturer identified  
in point 4.

Signed for and on behalf of the manufacturer by:


Artur Kehrlé, CEO  
Name and Function

Ichenhausen, 28.09.2023  
Place and Date of Issue



Signature

CE marking

	
KLB Kötztal Lacke + Beschichtungen GmbH Günztalstraße 25 89335 Ichenhausen, GERMANY	
23	
PU-Beton4004-V1-092023	
DIN EN 13813:2003-01	
Synthetic resin screed mortar DIN EN 13813: SR-B2,0-AR0,5-IR4	
Fire behaviour	E <sub>ff</sub> -s1
Emission of corrosive substances	SR
Wear resistance BCA	AR 0,5
Adhesive tensile strength	B 2,0
Impact resistance	IR 4



Please consider the latest version of this product information on our website.

All stated information is based on our experience and technical preparation. We guarantee the correct and proper quality of our products. We do not assume any responsibility for the work not carried out by us, since we have no influence on the processing or processing conditions. We recommend on-site trials to be conducted in individual cases. With the publication of this new KLB statement of performance, all prior information loses validity. The latest version is available electronically on our website [www.klb-koetztal.com](http://www.klb-koetztal.com). In addition, our "General Terms and Conditions" apply.