

KLB-SYSTEM

PU 5000 RX Abstreukomponente

Reactive scattering component for PU 5000 RX

Packaging units

Article no.	Packaging	Content (kg)	Units/pallet
PU6402-26	Hobbock	25.00 kg	12
PU6402-25	Hobbock	25.00 kg	12
PU6402-27	Hobbock	25.00 kg	12

Product description

Scattering component in three tested slip-resistance grades R10, R11 and R12 according to DIN 51130 and BGR 181, as system component for **PU 5000 RX**.

Available variants:

PU 5000 RX Abstreukomponente R 10
PU 5000 RX Abstreukomponente R 11
PU 5000 RX Abstreukomponente R 12

Processing

The scattering takes place based on the respective indications in the product information of **KLB-SYSTEM POLYURETHAN PU 5000 RX** within the consumption quantities of approx. 1 to 2 kg/m² specified there, obtain advice if necessary.

Storage

Store in dry and at frost-free conditions. Ideal storage temperature is 15 - 20 °C / 59 - 68 °F. Bring to a suitable processing temperature before application. Tightly re-seal opened packages and use up the content as soon as possible.



Please consider the latest version of this product information on our website.

All stated information is based on our experience and technical preparation. We guarantee the correct and proper quality of our products. We do not assume any responsibility for the work not carried out by us, since we have no influence on the processing or processing conditions. We recommend on-site trials to be conducted in individual cases. With the publication of this new KLB product information, all prior information loses validity. The latest version is available electronically on our website www.klb-koetztal.com. In addition, our "General Terms and Conditions" apply.