

## KLB-SYSTEM REINIGER VR 119

Solvent mixture for cleaning acrylic resins

### Packaging units



Article no.	Packaging	Content (kg)	Units/pallet
MA0010-55	Canister	10.00 l	50
MA0010-02	Drum	200.00 l	2

### Product characteristics

Classification	Highly flammable
----------------	------------------

### Product description

Solvent mixture to clean tools used for acrylic resin works. With strong dissolving effect suitable for tool cleaning, even after slight hardening of the resins.

Old acrylic resin-based coatings can be easily dissolved by wiping over **VR 119** for further recoating with new acrylic resin coatings or sealers.

**Note:** not recommended as thinner for acrylic resins.

### Technical data

Density	0.95	kg/l	DIN EN ISO 2811-2 (20 °C / 68 °F)
Flashpoint	10 °C / 50 °F	-	

The values established in tests are average values. Deviations from the product specification may occur.

### Processing

To clean tools, remove the necessary amount into a separate, reclosable container and carry out the cleaning with a brush. If necessary, tools with hardened material can be soaked in the dilution to remove the soiling.

### Storage

Always re-seal and close tight after usage and store closed in a dry place. Please note the safety data sheet!

**Special remarks**

Highly flammable. Note the information on the containers and on the safety data sheet.



Please consider the latest version of this product information on our website.

---

All stated information is based on our experience and technical preparation. We guarantee the correct and proper quality of our products. We do not assume any responsibility for the work not carried out by us, since we have no influence on the processing or processing conditions. We recommend on-site trials to be conducted in individual cases. With the publication of this new KLB product information, all prior information loses validity. The latest version is available electronically on our website [www.klb-koetzal.com](http://www.klb-koetzal.com). In addition, our "General Terms and Conditions" apply.

---