

CHEMORESIN PU-BETON 4004



According Attachment III Regulation (EG) No. 305/2011 (Building Product Regulation)

1. Unique identification code for the product type:

EN 13813:2003-01 - PU-Beton4004-V1-032026

Type, batch or serial number or any other element allowing identification of the building product as required according to article 11 (4):

Batch number: see label of the product

Intended use or usage of the building product, in accordance with the applicable harmonised technical specification, as intended by the manufacturer:

EN 13813: Synthetic resin screed mortar for internal use

Name, registered trade name or registered trade mark and contact address of the manufacturer as required according to article 11 (5):

KLB Kötztal Lacke + Beschichtungen GmbH
Günztalstraße 25
D-89335 Ichenhausen

System or systems for evaluation and verification of performance reliability for the building product according to annex V:

EN 13813:
System 4 (for internal use)
System 4 (for internal use subject to fire-behaviour regulations)

Notified Bodies (N):

EN 13813, System 4: -

In case of the declaration of performance concerning a building product for which a

Not relevant

European Technical
Assessment has been
issued:

Declared performance:


Harmonised technical specification	EN 13813:2003-01
------------------------------------	------------------

The performance of the
product according to
point 1 and 2 conforms
with the declared
performance in point 9.
This declaration of
performance is issued
under the sole
responsibility of the
manufacturer identified
in point 4.

Signed for and on behalf of the manufacturer by:

Artur Kehrlé, CEO
Name and Function

Ichenhausen, 04.03.2026
Place and Date of Issue



Signature

CE marking

CE	
KLB Kötztal Lacke + Beschichtungen GmbH Güntalstraße 25 89335 Ichenhausen, GERMANY	
23	
PU-Beton4004-V1-032026	
DIN EN 13813:2003-01	
Synthetic resin screed mortar DIN EN 13813: SR-B2,0-AR0,5-IR4	
Fire behaviour	B _{ff} -s1
Emission of corrosive substances	SR
Wear resistance BCA	AR 0,5
Adhesive tensile strength	B 2,0
Impact resistance	IR 4



Please consider the latest version of this product information on our website.

All stated information is based on our experience and technical preparation. We guarantee the correct and proper quality of our products. We do not assume any responsibility for the work not carried out by us, since we have no influence on the processing or processing conditions. We recommend on-site trials to be conducted in individual cases. With the publication of this new KLB statement of performance, all prior information loses validity. The latest version is available electronically on our website www.klb-koetztal.com. In addition, our "General Terms and Conditions" apply.