


KLB-SYSTEM partiColor®-Metalize

Coloured pearlescent pigments for designing Metalize floor coverings

Packaging units



Article no.	Color	Packaging	Content (kg)
ZG1024-92	partiColor®-Metalize Green	Bucket combo	kg
ZG1025-92	partiColor®-Metalize Blue	Bucket combo	1.00 kg
ZG1022-92	partiColor®-Metalize Bronze	Bucket combo	1.00 kg
ZG1020-92	partiColor®-Metalize Gold	Bucket combo	1.00 kg
ZG1027-92	partiColor®-Metalize Green	Bucket combo	1.00 kg
ZG1023-92	partiColor®-Metalize Pepper	Bucket combo	1.00 kg
ZG1026-92	partiColor®-Metalize Red	Bucket combo	1.00 kg
ZG1021-92	partiColor®-Metalize Silver	Bucket combo	1.00 kg

Product description

Coloured pearlescent pigments for the decorative design of KLB Metalize coverings. A decorative Metalize effect is achieved by mixing the pigments into a transparent sealer, e.g. **KLB-SYSTEM POLYURETHAN PU 484** or **KLB-SYSTEM POLYUREA PU 485 Flex**, which is then applied to a smooth coating. The **partiColor®-Metalize** pigments are available in various metallic-looking colours, see also the corresponding colour chart.

Included in systems

- [System G11 - KLB DECOR LOW-VOC PU Metalize Effect](#)

Please visit our website to get more information about our KLB systems: www.klb-koetzal.com

Processing

For detailed application instructions, please refer to the Metalize installation recommendation.

Prepare the substrate as usual by shot-blasting and prime with KLB priming resins and, if necessary, apply a scratch coat. Apply a base coat of **KLB-SYSTEM POLYURETHAN PU 410** in a suitable colour shade. This colour shade of the coating **KLB-SYSTEM POLYURETHAN PU 410** as well as of the **partiColor®-Metalize** pigment must be adapted according to the respective requirements, see the recommendations of KLB Kötztal in the **partiColor®-Metalize** colour selection as below.

Add the **partiColor®-Metalize** pigment to the A-component of **KLB-SYSTEM PU 484** or **KLB-SYSTEM PU 485 Flex** and mix homogeneously with a slow-running stirrer. Consumption approx. 1 % of **partiColor®-Metalize** pigment added to the total quantity of **KLB-SYSTEM PU 484** and **KLB-SYSTEM PU 485 Flex**.
Comp. A + B. Subsequently add the hardener, then mix again thoroughly and repot.

Storage

Store dry!



Please consider the latest version of this product information on our website.

All stated information is based on our experience and technical preparation. We guarantee the correct and proper quality of our products. We do not assume any responsibility for the work not carried out by us, since we have no influence on the processing or processing conditions. We recommend on-site trials to be conducted in individual cases. With the publication of this new KLB product information, all prior information loses validity. The latest version is available electronically on our website www.klb-koetzal.com. In addition, our "General Terms and Conditions" apply.