

KLB-SYSTEM POLYURETHAN PU 9030 Flex



According Attachment III Regulation (EG) No. 305/2011 (Building Product Regulation)

1. Unique identification code for the product type:

EN 13813:2003-01 - PU9030-V1-122023

Type, batch or serial number or any other element allowing identification of the building product as required according to article 11 (4):

Batch number: see label of the product

Intended use or usage of the building product, in accordance with the applicable harmonised technical specification, as intended by the manufacturer:

EN 13813: Synthetic resin screed mortar for internal use

Name, registered trade name or registered trade mark and contact address of the manufacturer as required according to article 11 (5):

KLB Kötztal Lacke + Beschichtungen GmbH
Günztalstraße 25
89335 Ichenhausen
GERMANY

System or systems for evaluation and verification of performance reliability for the building product according to annex V:

EN 13813:
System 4 (for internal use)
System 4 (for internal use subject to fire-behaviour regulations)

Notified Bodies (N):

EN 13813, System 4: -

In case of the declaration of performance concerning a building product for which a European Technical Assessment has been issued:

Not relevant

Declared performance:

| | |
|------------------------------------|------------------------|
| Essential characteristics | See attached CE-Symbol |
| Performance | See attached CE-Symbol |
| Harmonised technical specification | EN 13813:2003-01 |

The performance of the product according to point 1 and 2 conforms with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Artur Kehrlé, CEO
Name and Function

Ichenhausen, 08.12.2023
Place and Date of Issue



Signature

CE marking

| | |
|---|---------------------|
|  | |
| KLB Kötztal Lacke + Beschichtungen GmbH Günztalstraße 25 89335 Ichenhausen, GERMANY | |
| 13 | |
| PU9030-V1-122023 | |
| DIN EN 13813:2003-01 | |
| Synthetic resin screed mortar DIN EN 13813: SR-B1,5-AR0,5-IR4 | |
| Fire behaviour | E _{fl} -s1 |
| Emission of corrosive substances | SR |
| Wear resistance BCA | AR 0,5 |
| Adhesive tensile strength | B 1,5 |
| Impact resistance | IR 4 |



Please consider the latest version of this product information on our website.

All stated information is based on our experience and technical preparation. We guarantee the correct and proper quality of our products. We do not assume any responsibility for the work not carried out by us, since we have no influence on the processing or processing conditions. We recommend on-site trials to be conducted in individual cases. With the publication of this new KLB statement of performance, all prior information loses validity. The latest version is available electronically on our website www.klb-koetzal.com. In addition, our "General Terms and Conditions" apply.